

	MODEL	Picture		
1	HST-410R (R-0.8s-4m)		High Speed Drop Arm Barrier Gate Arm Length 4 m Operation Times 0.8s (s) Case on the right side, and boom on the right-side Temperature: -35°C to 80° Voltage AC 230V (+/-10%), 50Hz Motor Power 24 VDC Power Consumption 150W Remote control distance: 30m Chassis thickness: 1.5mm Weight 30 KG	
2	HST-410L (L-0.8s-4m)		High Speed Drop Arm Barrier Gate Arm Length 4 m Operation Times 0.8s (s) Case on the left side, and boom on the right-side Temperature: -35°C to 80° Voltage AC 230V (+/-10%), 50Hz Motor Power 24 VDC Power Consumption 150W Remote control distance: 30m Chassis thickness: 1.5mm Weight 30 KG	

3	HST-610R (R-3s-6m)	High Speed Drop Arm Barrier Gate Arm Length 6 m Operation Times 3s (s) Case on the right side, and boom on the right-side Temperature: -35°C to 80° Voltage AC 230V (+/-10%), 50Hz Motor Power 24 VDC Power Consumption 150W Remote control distance: 30m Chassis thickness: 1.5mm Weight 30 KG	
4	HST-610L (L-3s-6m)	High Speed Drop Arm Barrier Gate Arm Length 6 m Operation Times 3s (s) Case on the right side, and boom on the right-side Temperature: -35°C to 80° Voltage AC 230V (+/-10%), 50Hz Motor Power 24 VDC Power Consumption 150W Remote control distance: 30m Chassis thickness: 1.5mm Weight 30 KG	