



HST - 31B200 - M2712-IRAP



HST-31B200-M2712-IRAP

2.0MP Starlight & Ultra WDR HD Network Vandal-Proof Varifocal IR Semi Dome

Features

Excellent Image Quality

2.0 Megapixel 1/2.8" progressive scan CMOS sensor

High definition and smooth picture, 1080p@30fps

H.265 video codec, saves up to 50% bandwidth and storage

Ultra low illumination, 0.002lux with color picture

120dB Ultra WDR

3D noise reduction / Auto Iris / HLC

Intelligent Functions

Motion detection / Tampering / Guard line / Enter guard area / Exit guard area

Vandal-Proof

Above IK10 @ 50J collision energy

Integrated High Efficiency IR

Industrial IR LED with long operational lifespan

20 ~ 40m IR distance

Smart IR function

A Variety of Installation Modes

Supports 90°, 180°, 270° image rotation

Motorized varifocal lens

Abundant Functions and Features

Micro SD card slot, supports Automatic Network Replenishment (ANR)

Up to 3 Multi-stream

PoE

IP67



HST-31B200-M2712-IRAP	
Camera	
Image Sensor	1/2.8" progressive scan CMOS
Pixels	2.0 Megapixel
Min. Illumination	Color: 0.002lux@ (F1.6, AGC ON) B/W: 0.0002lux@ (F1.6, AGC ON); 0lux with IR
Shutter Speed	1 ~ 1/30,000s
Day / Night	Auto (ICR) / Color / B/W
Wide Dynamic Range	Ultra WDR, >=120dB
S/N Ratio	>50dB
White Balance	Auto / Manual
Gain Control	Auto / Manual
Backlight Compensation	Off / BLC / WDR / HLC
Lens	
Mount Type	Ø14
Auto Iris	DC drive
Focal Length	-Z2712: 2.7~12mm @ F1.6 motorized varifocal lens
Focus Control	Manual / Semi-Automatic / Auto
Angle of View	-Z2712: 106° ~ 33°
Adjustment Range	Pan: -120° ~ +120° / Tilt: 0° ~ 65° / Rotation: -90° ~ +90°
Infrared	
IR Distance	20 ~ 40m
IR Intensity	Smart IR
Video	
Compression	H.265 / H.264 / MJPEG
Image Resolution	Main stream: 1080p Secondary stream: D1 (1080p optional)
Frame Rate	Main stream: 1080p@30fps Secondary stream: D1@30fps (1080@12fps optional)
Bitrate	32kbps ~ 16Mbps
Bitrate Control	VBR / CBR
Multi-stream	Supported
Caption	Date and time / Alarm / Customized
Privacy Masking	Up to 4 zones
Motion Detection	Up to 4 zones
Video Freeze	Supported
ROI	Supported
Digital Noise Reduction	3D noise reduction
Digital Defog	Supported
Image Flip	Flip / Mirror / Rotation at 90°, 180°, 270°
Network	
Network Protocols	TCP/IP, UDP, HTTP, DHCP, DNS/DDNS, RTP/RTCP, RTSP, PPPoE, FTP, VSIP, UPnP, 802.1x, NAT, QoS, SMTP, IPv4, IPv6 (optional)
User Interface	IPC Control (IE, Firefox, Chrome)
Max. User Access	Max. 10 Users (includes 2 internal)
Application Programming	ONVIF (Profile S, Profile G), GB/T 28181-2011, API, CGI
Automatic Network Replenishment (ANR)	Supported
Alarm	
Alarm Triggers	Network disconnect / Disk full / Disk error



Intelligent	Motion detection / Tampering / Guard line / Enter guard area / Exit guard area
Alarm Events	Alarm report / Recording / Text overlay / Snapshot / Email notice
Interfaces	
Ethernet	10/100M, RJ45 interface
Memory Slot	Micro SD card slot, supports up to 128GB
Environmental	
Operating Temperature	-40°C ~ 70°C / -40°F ~ 158°F
Operating Humidity	10% ~ 95%
Protection Level	IK10+ @50J, IP67
Electrical	
Power	DC12V ± 10% / PoE (IEEE802.3af)
Power Consumption	Max. 11W
Mechanical	
Weight	0.71 kg / 1.57lb (Gross Weight)
Dimensions	Φ122× 96.13mm / Φ4.8" x 3.78"