



HST-H118C RFID Card Hotel Lock



FEATURES:

1. US RFID card-125Khz or M 1 card 13.56Mhz to unlock
2. Metal panel, anti-oxidation surface treatment, durable use
3. Free handles prevent vandalism
4. Unique hidden mechanical key hole design
5. ANSI standard five latches structure guarantee security
6. False-closing alarm: light and voice warning after incomplete closing
7. Compact lock body structure, good mechanical linkage
8. Circuit board: microcomputer chip control, more stable
9. Low working voltage alarm.
10. Color: Golden or Silver

Technical Parameter:

Material	Stainless steel 201
Panel Sizes	242*77*69mm
Accepted Door Thickness	38-55mm
Card Type	Temic card or M1 card
Working Voltage	DC 6V, 4pcs AA alkaline batteries
Starting Time	<1 second
Sensor Distance	3~5cm
Static Power Consumption	<4 μ A
Dynamic Power Consumption	About 200 mA
Low Voltage warning	Yes
Unlocking Way	Cards, Mechanical keys
Working Temperature	-20 to 50 $^{\circ}$ C
Working Humidity	\leq 80%
Lock Weight	2.8~3.4kg
Warranty	One year, lifetime maintenance

Hotel Lock System Composition:

1. Hotel Lock (qty = guest room) ---For open the door
2. Card Reader (1pcs/hotel) ---For issuing all kinds of cards
3. Energy Saving Switch (qty = guest room) ---To get the power
4. RFID Cards (qty = 3 times of guest room) ---For open the lock
5. Data collector (1pcs/hotel, optional) -----For getting the time and times of entrance infor from the lock.
6. Hotel management software (free of charge)----For setting the program the whole system.