

151

H51

R

2

٥

HST

RFID



6

SOS

HST-WIP



- TFT large digital display screen 4.3-inch.
- Date/clock/arm/disarm/cutdown time indication,
- Support up to 100 learning/storage location for remote control and wireless detector,
- Record 20 seconds alarm voice, if alarm occurs the alarm host will diall preset number and play the record voice.
- Support Wi-Fi/GSM/3G/GPRS network alarm system.
- Support 5 groups preset alarm phone number, SMS on/off and dial on/off can be set respectively, 7, Support SMS alarm/disarm and voice alarm/disarm

HST WPD/WDS

Security accessories

HST-WPD

specification

- Working voltage: 3V AA*2 alkaline battery
- Static current: ≤ 15uA
- Working current: ≤ 25mA
- Wireless data code: 1527 max area: 12mX12m
- Wireless Frequency: 433.92MHz 868.4MHz(optional)

Main feature

- binary infrared detection elements
- high intelligent ,high sensitivity
- detective range can get to 12m pan angel 1100 tilt angel 600
- Adopts CMOS low-power consumption microprocessor low power consumption
- The battery with a longer life built-in Millions of codes

HST-WDS

- Wireless Door sensor:
- Door Magnet is a detector used to detect illegal door prying and window entry.

specification

- Working voltage: DC3V
- Emission frequency: 315MHZ/433MHZ
- Coding Method: EV1527
- Action distance: 25-35MM
- Emission distance: ≥ 120M (open space)
- Low Pressure Alarm: 2.2-2.4V





HST-WRC

WiFi+CSM/3G alarm system

Specification

- Working voltage: DC 3V
- Working current: 15mA
- Wireless frequency: 315MHz/433MHz (optional)
- Oscillation mode: ev1527
- Emission distance: 80-150m

Main Features

- Coding mode: support both 1527/2262
- 80m range wireless transmitted in the open area
- Global used standard wireless transmit, ASK modulation transmit

HST-MWS

Specification

- Working Power: DC5V-3V(Cell coin battery)
- Working current: ≤ 15mA
- Standby current: ≤ 5uA
- VDC: 110±3

Main Feature

- Innovative waterproof design, prevent the water get into
- High quality ABS material, greens environmental protection
- Long range transmit, Reduce the probability of string code



